

NeoCycler 200 - Gradient Thermal Cycler

#Cat: NB-12-3002

Size: 1Unit

Features :

1. Newest Generation Peltier-based Technology, more Steady, Reliable and Durable

2. 7" Color Full Touch Screen, Graphical Display of Protocols

3. Effortlessly Interchangeable Reaction Modules that Swap in Seconds without Tools.

- 4. Unlimited storage of Protocols with USB Flash Drive
- 5. Update software with USB Flash Drive

The NeoCycler 200 is provide with a 9677 / 96 module.



Optional modules (WithGradient)

Cat#	Model	Capacity		
NB-12-3004	9677 / 96 Gradient	96 wells×0.2ml+77 wells×0.5ml		
NB-12-3006	Multi-purpose Gradient	9677 Module + In-situ Adapter		

Temperature


Block Temperature Range:	0°C~100°C		
Max. Ramping Rate:	5°C/sec		
Temperature Uniformity:	<pre></pre>		

Heat Lid

Innovative Designed Two-in-One (Open/Lift) Lid Auto Shut-off Heating Function of Lid at Low Temperature (<30°C) of block Steplessly Adjustable Lid, accommodates all kinds of PCR tubes, strips and plates



Max.30 Steps 100 Typical Cycles, max. 60,000 nesting cycles Time/Temp. Increment/Decrement is available for performing Long PCR and Touchdown PCR





Auto Pause; Auto restart after power failure

An Infinite incubation time at low temperature for overnight working

Multi-user log in with password-based authentication prevents from view, copy and alteration of protocols, ensure user's privacy and safety

Tm calculator automatically calculates the melting and annealing temperature through input two primer sequences, greatly improve work efficiency

Program wizard provides a quick method for creating PCR protocols in a few stepsDisplay recent run 10 programs for easy access

Get detailed running report, providing objective and precise information for the whole experiment Effortlessly Combine up to 50 units of A100/200 for remote control and management by computers

Pre-denaturation		Time(H			1	2	1
Denaturation	194		:50	1	-	5	4
Annaling	55		:50	1	7	T	-
V Extension	15	1] dos		-	-
Post-extension	\overline{n}	2	1		9	-	4
🗸 1841	1		-	V foreme			



Other Features

Wide Range Power Supply 85V-265V, 47-63Hz Communication Ports: USB2.0, LAN and RS232 Power Consumption : Max.600W Certificate: ISO 9001:2000, CE, RoHS Dimension (L×W×H) : 362×256×255mmNet Weight: 7.3kgs



Cat#	Description	
NB-12-3002	002 NeoCycler 200 - Gradient Thermal Cycler (with 9677 / 96 module)	